

Val-Tex Valve Flush



"Quality That Pays For Itself"



“IF THE LABEL DOESN’T SAY VAL-TEX, IT’S NOT VALVE FLUSH”

Val-Tex Valve Flush cleans out hardened sealants and lubricants that contain solids and / or fillers in all types of valves. This superior product is formulated using non-petroleum oils.

Valve Flush does not contain acid, caustic, solvent, or solids to add to your problems. Valve Flush is a safe, biodegradable, non-hazardous material. It is generally compatible with all lubricants and sealants.

After Valve Flush has freed your valve, follow with Val-Tex lube sealants. They are free of solids and fillers and eliminate the need for products like **Valve Flush**.

Val-Tex Valve Flush is available in the following packaging for use with standard valve lubrication equipment.

Part No.	Description	Weight		Suggested Injection Equipment
		Lbs.	Kilos.	
VF-CTN	4-2 lb. bottles	8	3.63	1400, QS-2000A, QS-2200A 1000-31, 6268A-13, MM
VF-GAL	1 Gallon Jug	8	3.63	QS-5000, QS-5000-C
VF-10	5 Quart Can	10	4.53	5-70, 10-70
VF-40	5 Gallon Pail	40	18.14	40-70
VF-120	16 Gallon Drum	120	54.43	On Request
VF-440	55 Gallon Drum	440	199.58	On Request

**STOP VALVE PROBLEMS BEFORE THEY START
USE VAL-TEX LUBE SEALANTS**

Stem and Thread Compounds

10-S Stem and Thread Lubricant - Temperature Range: 10° F to 350° F

Superior weather resistant thread and stem lubricant that helps to retard corrosion. Apply sparingly. Color: silver. Packaged In Zip Top Tubes, 1lb./.45 kg. cans, 10 lb./4.53 kg. cans, 40 lb./18.14 kg. pails, 120 lb./54.43 kg. drums and 440 lb./199.58 kg. drums.



19-S Thread Compound - Temperature Range: 10° F to 400° F

Seals and protects threads. Highly resistant to corrosion. Prevents galling of threads. Ideal for stainless to stainless threads. Packaged in Zip Top Tubes, 1 lb./.45 kg. cans, 10 lb./4.53 kg. cans, 40 lb./18.14 kg. pails, 120 lb./54.43 kg. drums, and 440 lb./199.58 kg. drums.

10600 FALLSTONE ROAD • HOUSTON, TEXAS 77099-4390 • ORDER 1-800-627-9771 • PHONE (281) 530-4848 • FAX (281) 530-5225 • WWW.VALTEX.COM